

6" 2-WAY FULL RANGE IN-CEILING SPEAKERS



CODE	PEAK POWER
MS-CL602	120 WATTS



KEY FEATURES

DISCREET FLAT MOUNT PROFILE

Designed with subtle aesthetics to blend in with the interior of your vessel, the 6" MS-CL602 in-ceiling speakers feature a discreet flat mount profile.

These versatile speakers can be installed both in the ceiling or on the wall, with the flat profile eliminating the chance of damage from people or objects passing by.

SMOOTH, CLEAR AUDIO REPRODUCTION

The combination of a silk dome tweeter and high quality polypropylene cone ensures smooth, clear reproduction of sound for a quality in-cabin audio entertainment experience.

6 OHM IMPEDANCE

With 6 ohm impedance, the MS-CL602 speakers are designed to integrate with a variety of source units, to provide more freedom of choice when setting up your in-cabin audio entertainment system.

120 WATTS PEAK POWER

To ensure crisp and clear audio delivery all around the cabin, the 6" MS-CL602 in-ceiling speakers produce an impressive 120 watts peak power.

SUPER SOUND QUALITY FROM A SHALLOW MOUNT FORM FACTOR

Sophisticated engineering has resulted in a speaker with superb sound quality from a shallow mount basket, solving the quality issue many people face when trying to achieve great sound from a shallow form factor.

The shallow basket allows for speaker installation where mounting depth is limited, providing more options for speaker placement on board.

DESIGNED FOR EASY INSTALLATION

The MS-CL602 in-ceiling speakers are designed for simple installation, with no additional fasteners or adhesive mounts required to install the speakers.

Simply place the speaker in the cutout area, and the built-in mounting tabs will clasp the edges of the cutout to keep the speaker in place.

FUSION PRODUCT INFO

CODE	GARMIN PN	EAN-13 BARCODE	GIFT BOX DIMENSIONS
MS-CL602	MS-CL602		

FOR MORE INFORMATION VISIT FUSIONENTERTAINMENT.COM

SPECIFICATIONS

SPEAKER SIZE	6"
PEAK POWER (WATTS)	120
RMS POWER RATING (WATTS)	40
EFFICIENCY (1W/1M)	89dB
FREQUENCY RESPONSE	(-10dB/-3dB) 50Hz - 20kHz / 85Hz - 20kHz
IMPEDANCE	6 ohms
TWEETER TYPE	Silk dome
CONE/SURROUND MATERIAL	Polypropylene
MOUNTING DIAMETER CLEARANCE	205.5mm (8-1/16")
MOUNTING DEPTH CLEARANCE	77.6mm (3-1/16")
WARRANTY	1 year

DIMENSIONS

